

JONAS



Power^[W] / Luminosity^[Lm]

- 36 W > 425 Lm
- 54 W > 595 Lm
- 72 W > 1020 Lm
- 40 W > 1275 Lm



General information

- Mounting type: Embedded
- Type LED: SMD
- Voltage: 12/24 VDC - 240 VAC
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 15/30/40/60

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- The Jonas LED luminaire is an outdoor fixture, recessed into outdoor floors, made of high quality materials, finished to meet the highest customer demands.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- Transparent PMMA disperser

JONAS

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
JON36W-S	36	425	12	6000K	Φ250x190 - Φ223	1.8
JON36NW-S	36	425	12	4000K	Φ250x190 - Φ223	1.8
JON36WW-S	36	425	12	3000K	Φ250x190 - Φ223	1.8
JON36RGB-S	36	425	12	RGB	Φ250x190 - Φ223	1.8
JON54W-S	54	595	12	6000K	Φ250x190 - Φ223	1.8
JON54NW-S	54	595	12	4000K	Φ250x190 - Φ223	1.8
JON54WW-S	54	595	12	3000K	Φ250x190 - Φ223	1.8
JON54RGB-S	54	595	12	RGB	Φ250x190 - Φ223	1.8
JON72W-S	72	1020	14	6000K	Φ250x190 - Φ223	1.8
JON72NW-S	72	1020	14	4000K	Φ250x190 - Φ223	1.8
JON72WW-S	72	1020	14	3000K	Φ250x190 - Φ223	1.8
JON72RGB-S	72	1020	14	RGB	Φ250x190 - Φ223	1.8
JON40W-S	40	1275	32	6000K	Φ250x190 - Φ223	1.8
JON40NW-S	40	1275	32	4000K	Φ250x190 - Φ223	1.8
JON40WW-S	40	1275	32	3000K	Φ250x190 - Φ223	1.8
JON40RGB-S	40	1275	32	RGB	Φ250x190 - Φ223	1.8

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	Yes	NA	NA	NA	NA